

MIP480 In-Vehicle Printer

Fixed Vehicle Printer for Heavy Duty Workload



Product Highlights

- Rugged construction
- Easy paper loading
- Simple to change long life ribbon
- Can handle fan fold and cut sheet forms
- Print speed up to 480 cps
- Backlit control panel
- Bluetooth and 802.11 connectivity available

High speed, easy to use vehicle printer

Ideally suited to route delivery and other Mobile Applications.

Paper Loading

Paper loading is done without opening covers, and paper stabilizer guides provide a solid backing for easy location (tractor cover included for harsh environments).

Ribbon Changing

The MIP480 uses a long life 4 mil character ribbon - in typical usage, this means you only have to change ribbons once every three or four months.

Forms Flexibility

The MIP480 can handle up to four part continuous forms - it can also print on single top glued forms giving you flexibility for future requirements.

Excellent Print Quality

The 24-wire print head produces clear, crisp output of text and graphics. There's support for IBM® Proprinter® X24e and Epson® ESC/P2 emulations. A variety of resident typefaces ensure fast, high-quality text.

Optional Accessories

Ruggedized brackets, paper input trays and vehicle power cords are also available for the MIP480. Custom hardware can be designed for your fleet if required.

Available Configuration:

MIP48000-AA Standard Model - includes RS232, USB, and Bluetooth

MIP48001-AA Optional Model - includes 802.11 plus connectivity of the standard model.

Features & Specifications

Print Speed	AT 10 cpi: 400 draft, 133 LQ; At 12 cpi: 480 draft, 160 LQ
Print Method	Serial impact dot matrix
Resolution	180 x 120 dpi Draft, 180 x 360 dpi LQ, 1 / 360" All-point-addressable
Character Density	10, 12, 15, 17.1, 20, 24
Line Density	3, 4, 5, 6, 8
Character Modes	Double width , Double height ,Double strike, Italic
Character Sets	Code pages 437, 850, 860, 862, 863, 865, 851, 852853, 855, 857, 866, 869, USSR Gost, 864, 437G 920 (Latin-5), 858, 923(Latin-9)
Standard Connectivity	RS232, USB 2.0, Bluetooth Ver 1.2
Optional Connectivity	802.11 wireless ethernet
Standard Emulation	IBM 2390+ (includes Pro printer XL24E), ESC/P2, Intermec 6820
Fonts	Draft, Roman, Sans Serif, Courier, Bold, Prestige, Script, Orator, Gothic, OCR-A, OCR-B, Sans Serif H, Roman T; Barcodes: UPC/A, UPC/E, EAN8, EAN13, Code 39, Code 128, Codabar, Interleaved 2 of 5, Industrial 2 of 5
Consumables	4 million character, re-inking ribbon
STD Paper Handling	continuous forms: park, manual paper thickness adjustment; cut sheets: auto-load
Number of Copies	original plus three
Paper Type	continuous forms, cut sheets
Paper Size	Continuous Forms: Width 4" - 10.5" (102-267 mm); Length 4" or more (102+ mm). Cut Sheet: Width 4-10.5" (102-267 mm); Length 3-14.3" (76-364 mm)
Physical Weight	15.4 lbs (7 kg)
PhysicalSize	14.2"w x 10.2"h x 4.7"d (36.0cm x 26.0cm x 12.0cm)
Power Voltage	AC Adapter: 110 VAC +/- 10%, 240 VAC +/- 10%; Printer 12-24 VDC
Power Frequency	AC Adapter: 60 Hz, 50 Hz
Compliance	CA C22.2 No. 950; EN60950; GS Mark; UL 746C; CE EMC Directive; E-Mark; ASTM, EC Directives, EU Directives
Drivers	Windows XP, 2000 ESCP/2
Temperature	-4°F to 140°F (-20°C to 60°C); Storage: -22°F to 158°F (-30°C to 70°C)
Acoustic	57 dB(A)
Warranty	One Year Return To Depot



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Printed Date: 11/13/2006 Copyright © 2006 TallyGenicom, L.P.

4500 Daly Drive, Suite 100
Chantilly, VA 20151
T 800.436.4266
www.tallygenicom.com